

ICR-600VD

600TVL IP68 2.8-12MM VANDAL PROOF DOME



Features

- 600 TV Line Resolution
- True Waterproof (IP68)
- 1/3" Sony Super HAD CCD II
- Day and Night Function
- 0.1Lux at F1.2 (Colour) / 0.01Lux (B/W)
- 2DDNR (2D Digital Noise Reduction)
- Controlled by OSD Menu
- DC iris control
- Privacy Function
- Motion Detection
- Easy Installation & 3-Axis

Specifications

| SPECIFICATION | ICR-600VD |
|------------------------------------|---|
| Resolution | 600 TV Lines |
| Sensor | 1/3 inch SONY Super HAD CCD II |
| Total Pixels | 811(H) x 508(V) 410K pixels (NTSC) 795(H) x 595(V) 470K pixels (PAL) |
| Effective Pixels | 768(H) x 494(V) 380K pixels (NTSC) 752(H) x 582(V) 440K pixels (PAL) |
| Scanning System | 2:1 Interlace |
| S/N (Y signal) | More than 50 dB (AGC off) |
| Frequency | Horizontal : 15.734KHz / Vertical : 59.94Hz (NTSC) Horizontal : 15.625KHz / Vertical : 50.00Hz (PAL) |
| Video Output | CVBS : 1.0Vp-p / 75ohm |
| Min. Illumination | 0.1Lux at F1.2 (Colour) / 0.01Lux (B/W) |
| White Balance | ATW1 / ATW2 / AWC-SET / MANUAL Adjustable |
| Electronic shutter speed | Auto / Manual (1/60 sec ~ 1/100,000 sec NTSC) (1/50 sec ~ 1/100,000 sec PAL) |
| O.S.D | Built-in |
| Backlight Compensation | OFF / BLC / HLC Selectable |
| AGC (Auto Gain Control) L | OW, MIDDLE, HIGH, OFF Selectable |
| 2DDNR (2D Digital Noise Reduction) | ON/OFF |
| Day & Night | AUTO / COLOR / BW / EXT |
| Motion Detection | OFF / ON (Motion size : 28 x 15, 4 AREA) |
| PRIVACY | OFF / ON (8 Zone) |
| Image Conversion | ON / OFF |
| SHARPNESS | ADJUSTABLE |
| Operating Temperature/Humidity | -10°C ~ +50°C / 30% ~ 80% RH |
| Storage Temperature /Humidity | -20°C ~ +60°C / 20% ~ 90% RH |
| Power | DC12V |
| LENS | Auto Varifocal Lens 2.8-12mm |